

DUALIFT

THE HIGH PRODUCTION HOIST

PATENT PENDING



SERVICES BOTH CABLE AND HOOK CONTAINERS!

HAULS ANY LENGTH CONTAINER AND ANY HOOK HEIGHT

PRECISELY LOADS PUP TRAILERS, DOCKS AND FLATBEDS

SAFER OPERATION AND REDUCED MAINTENANCE COSTS

INCREASED PRODUCTIVITY AND PROFITS!



DUALIFT Standard Features:

- ✓ Collapsible rear under-ride
- ✓ Poly fenders
- ✓ Steel side mount hydraulic oil tank
- ✓ Safety Props
- ✓ Mid-turn signal
- ✓ Back-up & hoist-up alarms
- ✓ Side rollers (5/side) 4" OD x 3-1/2" L greaseable bronze bushings with outboard support
- ✓ Design allows single tire pusher axle
- ✓ Outside valve control
- ✓ Shut off valve 2", 1/4 turn full-flow
- ✓ Rear container hold-down strap
- ✓ Enclosed 8-1/4" rear roller greaseable

Model	HC6022	HC6024
Capacity - cable	60,000 lbs.	60,000 lbs.
- hook	65,000 lbs.	65,000 lbs.
Container lengths	12' to 22'	12' to 24'
Cab to Tandem	184"	204"
Hook Height	36", 54" and 62"	
Cylinders:		
lift, carriage, hook	6", 7", 4"	
Hydraulic pump	50 gpm	
Filter	High pressure full flow	
Operating pressure	2500 psi max	
Dump angle	50°	
Frame	9" channel 2"x4" sub-frame	
Rear Hinge	2-1/2"	
Sheave (one)	14"	
Cable length (7/8")	28 feet	30 feet
Cable anchor end	Terminator wedge	

DUALIFT Available Options:

- ✓ Pintle Hook frame assembly
- ✓ Pintle Hook
- ✓ LED lights
- ✓ Automatic tarper
- ✓ Tarper ready hydraulics
- ✓ Wet-line kit
- ✓ Fire extinguisher rack
- ✓ Air shift PTO
- ✓ Inside air controls
- ✓ Tool box
- ✓ Steel or Aluminum fenders
- ✓ Hook style rear container hold-down
- ✓ 54" high mast (54" & 36" lift bars)



DUALIFT is a better hook lift:

- Lower loading height and lift angle.
- Services container lengths 12'-24'
- Services lift bar heights 36", 54" & 62"
- Cable type frame rail stability
- Compliant rear under-ride.



DUALIFT is a better cable hoist:

- Twice the alignment forgiveness of reeving hoists
- Faster than reeving operations
- Breaks stubborn loads free
- Powers short containers to rear of frame before raising
- 10' cable at rear of hoist, excellent for tough pulls



DUALIFT loads pup trailers:

- Easy and fast loading.
- Controlled movement of hook *and* cable containers onto pup trailer.
- Safer method to load pup trailers.

Refuse Parts, LLC

PO Box 237, 3424 State Route 309

Iberia, OH 43325-0237

Phone: (419) 468-5095 Fax: (419) 462-1200

Email: info@refuseparts.com

Website: www.refuseparts.com

Distributed by: